



X1K2	
Motor Mount	SAE A 2 Bolt 128cc
Min. Hydraulic Flow	4 GPM (15Lpm)
Max. Hydraulic Flow	20 GPM (75Lpm)
Max. Continuous Pressure	3000 PSI (207 Bar)
Unit Weight	TBC
Output Shaft	2" Hex
Relief Valve	Internal to Motor
OUTPUT SPEED	
FLOW	SPEED
GPM (LPM)	RPM
4 (15.1)	28
6 (22.7)	42
8 (30.2)	56
10 (37.8)	70
12 (45.4)	84
14 (53)	98
16 (60.4)	112
18 (68.1)	126
20 (75.6)	140
OUTPUT TORQUE	
PRESSURE	TORQUE
PSI (BAR)	FT/LBS (Nm)
400 (28)	156 (212)
600 (41)	234 (317)
800 (55)	311 (422)
1000 (69)	389 (528)
1200 (83)	467 (633)
1400 (97)	545 (739)
1600 (110)	623 (845)
1800 (124)	701 (951)
2000 (138)	778 (1055)
2200 (152)	856 (1161)
2400 (166)	934 (1261)
2600 (179)	1012 (1372)
2800 (193)	1090 (1478)
3000 (207)	1168 (1584)
Note: 1 Ftlb = 1.356 Nm	