



X20K

Motor Mount	SAE "CC" 4 Bolt
Motor	500.0cc Bidirectional Speed
Min. Hydraulic Flow	10 GPM
Max. Hydraulic Flow	40 GPM
Max. Continuous Pressure	3000 PSI
Unit Weight	571 Lbs.
Output Shaft	3" Hex

OUTPUT SPEED

FLOW GPM (LPM)	SPEED RPM
10 (38)	3.6
12 (45)	4.3
15 (57)	5.4
17 (64)	6.1
20 (76)	7.2
22 (83)	7.8
25 (96)	8.9
27 (102)	9.7
30 (114)	10.7
32 (121)	11.5
35 (133)	12.5
40 (151)	14.3

OUTPUT TORQUE

PRESSURE PSI (BAR)	TORQUE FT/LBS (Nm)
1000 (69)	6890 (9343)
1200 (83)	8268 (11211)
1400 (96)	9646 (13080)
1600 (110)	11024 (14949)
1800 (124)	12402 (16817)
2000 (138)	13780 (18686)
2200 (152)	15158 (20554)
2400 (166)	16536 (22422)
2600 (179)	17914 (24291)
2800 (193)	19292 (26160)
3000 (207)	20670 (28029)

Note: 1 Ftlb = 1.356 Nm