



X1K8

Motor Mount	SAE A 2 Bolt 169cc
Min. Hydraulic Flow	4 GPM (15 Lpm)
Max. Hydraulic Flow	25 GPM (95 Lpm)
Max. Continuous Pressure	3500 PSI (241 Bar)
Unit Weight	TBC
Output Shaft	2" Hex

OUTPUT SPEED

FLOW	SPEED
GPM (LPM)	RPM
4 (15.1)	21
6 (22.7)	32
8 (30.2)	42
10 (37.8)	53
12 (45.4)	64
14 (53)	74
16 (60.4)	85
18 (68.1)	95
20 (75.6)	106
22 (83.3)	117
25 (94.6)	132

OUTPUT TORQUE

PRESSURE	TORQUE
PSI (BAR)	FT/LBS (Nm)
400 (28)	205 (278)
600 (41)	307 (417)
800 (55)	410 (555)
1000 (69)	512 (694)
1200 (83)	614 (833)
1400 (97)	717 (972)
1600 (110)	819 (1111)
1800 (124)	922 (1250)
2000 (138)	1044 (1416)
2200 (152)	1126 (1527)
2400 (166)	1229 (1666)
2600 (179)	1331 (1805)
2800 (193)	1434 (1944)
3000 (207)	1536 (2083)
3200 (221)	1638 (2222)
3500 (241)	1792 (2430)

Note: 1 Ftlb = 1.356 Nm